


## AUTOMATIC WEATHER SEAL

# LSR8301

A lever activated automatic weather seal, with high efficiency mechanism that lifts the seal clear of the floor as soon as you open the door by a few millimetres. It's quick and easy to install without cutting or removing the door and can be fitted to a range of door types.



AUTOMATIC WEATHER SEALS



LSR8301



LSR8301

### SYSTEM SPECIFICATIONS

#### Key benefits

- ▶ Suitable for many door types.
- ▶ Ideal for security screens.
- ▶ Quick & easy installation - no need to cut or remove the door.
- ▶ Flexible and durable.

#### Performance

- ▶ Protects against weather, cold, draught, light, sound insects and vermin.

#### Approvals

- ▶ Bushfire: Approved for use on fire door assemblies for Bushfire attack levels of BAL<29.

#### Location

- ▶ Opening side of the door.
- ▶ Closing side of the door.
- ▶ Overlay doors.

#### Gap sizes

- ▶ 3mm - 14mm.

#### Length

- ▶ 930mm - can be cut back to 150mm.

#### Seal material

- ▶ Tri-extruded plastic.

#### Fixing method

- ▶ LSR8301 is screw fixed onto the bottom of the door.
- ▶ Use the lever and stike plate for the opening side of a door.
- ▶ Use the lever and triangualr stike for overlay doors.
- ▶ Use the circular stike for the closing side of the door.

#### Finishes

- ▶ White with grey fixings.
- ▶ Brown with black fixings.