


DOOR BOTTOM SEALS

LAS3003 si

MEDIUM DUTY

Medium duty door bottom and meeting stile seals with slide-in gaskets; ideal for acoustic and smoke containment.



▲ LAS3003 si



DOOR BOTTOM SEALS

▲ LAS3003 si

SYSTEM SPECIFICATIONS

Key benefits

- ▶ Simple, effective sealing solution.
- ▶ Easily retrofitted to existing door assemblies.
- ▶ Durable, hard wearing silicone rubber gaskets.
- ▶ Protects against sound, smoke, weather, draught, light and insects.

Gap size

- ▶ 7mm/13mm.

Standard lengths

- ▶ 1m and 2.1m.
- ▶ Other lengths to special order.

Approvals

- ▶ **Smoke:** Conforms with BCA Specification C3.4 smoke sealing requirements.
- ▶ **Durability:** Long term mechanical test, completing 100,000 cycles without failure.

Fixing method

- ▶ Face-fixed, semi-rebated or fully rebated.
- ▶ Fixing screws are supplied.
- ▶ Fixing holes are pre-drilled.
- ▶ Once the aluminium carrier is fixed, the rubber gasket slides easily into place.
- ▶ Note: these seals cannot be adjusted once fitted.

Finishes

- ▶ Silver anodised aluminium with grey silicone rubber insert.