

Fitting instructions

Door bottom seal

LAS3004 si



Length:

Contents include

Cover strip
Aluminium carrier
Pre-drilled holes

Silicone gasket Bag of screws Fitting instructions

Tools required

Tape measure
Saw (power or hand)
Screw driver
2.5mm drill bit
Drill (power or hand)
Knife
Pencil or Marker

For further information about our products please visit our website

www.lorientgroup.com

t: +61 (02) 9905 0868

f: +61 (02) 9905 0883

e: admin@lorientau.com.au

Instructions

It is not necessary to remove the door from its hinges unless otherwise specified.

- Remove the seal from the packaging and measure the door width.
- 2. Remove the decorative cover strip from the aluminium carrier.
- **3.** Pull back silicone gasket and cut aluminium carrier to required length.
- **4.** Cut the decorative cover strip to the length required.
- **5.** Slide silicone gasket back into position and cut to required length.

Please note: Recommendations as to methods, use of materials and construction details are based on the experience and knowledge of Lorient and are given in good faith as a general guide and service to designers, contractors and manufacturers.

Lorient reserves the right to make alterations or delete installation detail without prior notice.

- **6.** Position the seal to the door bottom (as illustrated) and mark out the slotted hole locations with a pencil.
- **7.** Drill pilot holes with a 2.5mm drill bit (if required).
- 8. Lightly screw fix the length to the door bottom through the slotted holes with the screws supplied. (Fixing holes are pre- slotted to enable the seal to be accurately adjusted as required).
- **9.** Close the door and check for a uniform seal, adjust the seal if required.
- **10.** Tighten screws and replace the decorative cover strip.



Important

Ensure that the installation of this product does not impede the opening or closing of the door. It is recommended to check the adjustment of the door seal periodically to ensure the door assembly to which it is fitted, closes and latches properly.

We recommend the LAS3004 si be used together with a Lorient threshold plate.

Other Lorient products:

Acoustic, smoke & fire seals

Fire resistant glazing systems

Fire resistant door hardware

Air transfer grilles/ dampers



Lorient Pty Ltd Unit 30, 9 Powells Road Brookvale 2100 New South Wales Australia

+61 (02) 9905 0868 www.lorientgroup.com

All rights reservered. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient Polyproducts Limited.

© Lorient Polyproducts Ltd 2018