


DOOR BOTTOM SEALS

LAS3007 si

HEAVY DUTY

A heavy duty weather proof seal, which can be fitted without removing the door, and can be used with a choice of threshold plates. Concealed fixings, pre-drilled and slotted holes on LAS3007 si provide easy adjustment. Durable, anodised aesthetic finish.



▲ LAS3007 si



▲ LAS3007 si
shown with LAS4010

DOOR BOTTOM SEALS

SYSTEM SPECIFICATIONS

Key benefits

- ▶ Durable multi-bladed silicone seal.
- ▶ Snap-fit cover strip conceals fixing points.
- ▶ Slotted fixing holes provide simple adjustment.
- ▶ Aesthetic anodised finish.

Gap size

- ▶ 16mm/22mm.

Standard lengths

- ▶ 1m and 2.1m.
- ▶ Other lengths available to special order.

Approvals

- ▶ **Smoke:** Conforms with BCA Specification C3.4 smoke sealing requirements.
- ▶ **Durability:** Long term mechanical test, completing 100,000 cycles without failure.

Fixing method

- ▶ Self-tapping screws are supplied.
- ▶ Fixing holes are pre-drilled and slotted to allow the seals to be adjusted and positioned accurately. A snap-fit cover strip to conceal fixings is supplied.

Finishes

- ▶ Silver anodised aluminium with grey cover strip and grey silicone rubber blade.