

DOOR BOTTOM SEALS


LAS3008 si

MEDIUM DUTY

A multi-blade, storm-proof seal combination consisting of the LAS3007 si door bottom seal and LAS4015 threshold plate. Durable, anodised aesthetic finish. It can be fitted without removing the door. Concealed fixings, pre-drilled and slotted holes on LAS3007 si for easy adjustment.



DOOR BOTTOM SEALS



↑
LAS3008 si



SYSTEM SPECIFICATIONS

Key benefits

- ▶ Durable multi-bladed silicone seal.
- ▶ Snap-fit cover strip conceals fixing points.
- ▶ Slotted fixing holes provide simple adjustment.
- ▶ Aesthetic anodised finish.

Gap size

- ▶ 26mm/32mm.

Standard lengths

- ▶ 1m and 2.1m. Other lengths to special order.

Approvals

- ▶ **Smoke:** Conforms with BCA Specification C3.4 smoke sealing requirements.
- ▶ **Durability:** Long term mechanical test, completing 100,000 cycles without failure.

Fixing method

- ▶ LAS3007 si – Self-tapping wood screws are supplied (self-drilling and self-tapping screws for metal construction available on request). Fixing holes are predrilled and slotted to allow the seals to be adjusted and positioned accurately.
- ▶ A PVC cover strip to conceal fixings is supplied.
- ▶ LAS4015 – Fixing screws are supplied. PVC cover strip to conceal fixings is supplied.

Finishes

- ▶ LAS3007 si – Silver anodised aluminium with grey cover strip and grey silicone rubber gasket.
- ▶ LAS4015 – Silver anodised aluminium with grey cover strip.