


LDBU

HEAVY DUTY

This retro-fit seal is used to upgrade fire door assemblies that have a door bottom clearance that exceeds the 10mm specified in AS1905.1



DOOR UPGRADE SOLUTIONS



SYSTEM SPECIFICATIONS

Key benefits

- ▶ Simple screw fix installation.
- ▶ Suitable for upgrading door bottom gaps up to *24mm. Cost savings for building owners as non-compliant fire door assemblies may be simply salvaged rather than replaced.
- ▶ Incorporates a waterproof high performance graphite strip suitable for exterior applications.
- ▶ Durable silicone rubber gaskets.

Gap size

- ▶ Up to 24mm* maximum.
- ▶ *Please refer to our technical brochure "Retro-fit Sealing Solutions for Non-compliant Fire Door Assemblies" regarding maximum allowable gap sizes.

Approvals

- ▶ **Fire:** Tested in accordance with AS1530.4 on proprietary AS1905.1 fire door assemblies for up to 4 hour rating.
- ▶ **Bushfire:** Approved for use on proprietary fire door assemblies for Bushfire attack levels of Flame Zone (FZ) classification or less.

Fixing method

- ▶ Self-tapping screws are supplied.
- ▶ Fixing holes are pre-drilled and slotted to allow the seals to be adjusted and positioned accurately. A snap-fit cover strip to conceal fixings is supplied.

Standard lengths

- ▶ 820mm, 920mm, 1070mm and 1220mm.

Finishes

- ▶ Silver anodised aluminium with grey cover strip and grey silicone rubber blade.