




# LAS4010, LAS4011, LAS4012 & LAS4013

## MEDIUM DUTY


Medium duty, low profile aluminium threshold plates, only 6mm high. Ideal for wheeled traffic. These plates can increase the effectiveness of threshold (door bottom) seals by creating a firmer gasket contact; preventing rain, draught and smoke penetration.




LAS4010



LAS4011



LAS4012



LAS4013



LAS4010

### SYSTEM SPECIFICATIONS

#### Key benefits

- ▶ When used in conjunction with threshold (door bottom) seals, these plates prevent rain, draught & smoke penetration.
- ▶ Quick and easy installation
- ▶ Durable anodised aesthetic finish.

#### Gap sizes

- ▶ Minimum 6mm door undercut.

#### Fixing method

- ▶ Fixing screws are supplied.

#### Approvals

- ▶ **Fire:** Tested in accordance with AS1530.4 on proprietary AS1905.1 fire door assemblies up to 4 hour rating.
- ▶ **Sound:** Acoustically tested as part of a system in accordance with ISO10140-2 and AS/NZS717.1.
- ▶ **Bushfire:** Approved for use on proprietary fire door assemblies for Bushfire attack levels of Flame Zone (FZ) classification or less.

#### Standard lengths

- ▶ 1m, 2.1m and 3m.
- ▶ Other lengths available to special order.

#### Finishes

- ▶ Silver anodised aluminium.